查询CNA1009H供应商

CNZ1021 (ON1021), CNZ1023 (ON1023), CNA1009H (ON1024)

Photo Interrupter

For contactless SW, object detection

■ Overview

CNZ1021, CNZ1023 and CNA1009H are a transmissive photosensor in which a high efficiency GaAs infrared light emitting diode is used as the light emitting element, and a high sensitivity phototransistor is used as the light detecting element. The two elements are arranged so as to face each other, and objects passing between them are detected.

■ Features

- Highly precise position detection: 0.25 mm
- Gap width: 3 mm (CNZ1021, CNZ1023)
  5 mm (CNA1009H)
- The type directly attached to PCB CNZ1021
  Screw-fastened type (one side) CNZ1023
  The type directly attached to PCB CNA1009H
  (with a positioning pins)

CNZ1021 Unit: mm



1: Anode
2: Cathode
3: Collector
4: Emitter
PISTR104-001 Package

CNZ1023 Unit: mm



1: Anode
2: Cathode
3: Collector
4: Emitter
PISTR104-003 Package

CNA1009H Unit: mm



1: Anode
2: Cathode
3: Collector
4: Emitter
PISTR104-004 Package

(Note) 1. Tolerance unless otherwise specified is ±0.3
2. ( ) Dimension is reference

Note) The part numbers in the parenthesis show conventional part number.

■ Absolute Maximum Ratings $T_a = 25°C$

Parameter			Symbol	Rating	Unit
Input (Light emitting diode)	Reverse voltage	CNZ1021	V_R	3	V
		CNZ1023		3	
		CNA1009H		5	
	Forward current		I_F	50	mA
	Power dissipation *1		P_D	75	mW
Output (Photo transistor)	Collector-emitter voltage (Base open)		V_{CEO}	30	V
	Emitter-collector voltage (Base open)		V_{ECO}	5	V
	Collector current		I_C	20	mA
	Collector power dissipation *2		P_C	100	mW
Temperature	Operating ambient temperature		T_{opr}	−25 to +85	°C
	Storage temperature		T_{stg}	−40 to +100	°C

Note) ∗1: Input power derating ratio is 1.0 mW/°C at $T_a \geq 25°C$.
∗2: Output power derating ratio is 1.33 mW/°C at $T_a \geq 25°C$.

■ Electrical-Optical Characteristics $T_a = 25°C \pm 3°C$

Parameter		Symbol	Conditions	Min	Typ	Max	Unit
Input characteristics	Forward voltage	V_F	$I_F = 20$ mA		1.25	1.40	V
	Reverse current	I_R	$V_R = 3$ V			10	µA
Output characteristics	Collector-emitter cutoff current (Base open)	I_{CEO}	$V_{CE} = 10$ V		10	200	nA
Transfer characteristics	Collector current	I_C	$V_{CC} = 5$ V, $I_F = 20$ mA, $R_L = 100\ \Omega$	0.5		15.0	mA
	Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_F = 40$ mA, $I_C = 1$ mA			0.4	V
	Rise time *	t_r	$V_{CC} = 5$ V, $I_C = 1$ mA		5		µs
	Fall time *	t_f	$R_L = 100\ \Omega$		5		µs

Note) 1. Input and output are practiced by electricity.
2. This device is designed be disregarded radiation.
3. ∗: Switching time measurement circuit





t_r : Rise time
t_f : Fall time

I_F , I_C — T_a



I_F — V_F



V_F — T_a



I_C — I_F



I_C — V_{CE}



ΔI_C — T_a



I_{CEO} — T_a



t_r — I_C



ΔI_C — d



⚠ Caution for Safety

⚠ DANGER

■ This product contains Gallium Arsenide (GaAs).

GaAs powder and vapor are hazardous to human health if inhaled or ingested. Do not burn, destroy, cut, cleave off, or chemically dissolve the product. Follow related laws and ordinances for disposal. The product should be excluded form general industrial waste or household garbage.

Request for your special attention and precautions in using the technical information and semiconductors described in this material

(1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technical information described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.

(2) The technical information described in this material is limited to showing representative characteristics and applied circuits examples of the products. It neither warrants non-infringement of intellectual property right or any other rights owned by our company or a third party, nor grants any license.

(3) We are not liable for the infringement of rights owned by a third party arising out of the use of the technical information as described in this material.

(4) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
- Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
- Any applications other than the standard applications intended.

(5) The products and product specifications described in this material are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.

(6) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage, and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.

(7) When using products for which damp-proof packing is required, observe the conditions (including shelf life and amount of time let standing of unsealed items) agreed upon when specification sheets are individually exchanged.

(8) This material may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.